

Package: LogConcDEAD (via r-universe)

September 12, 2024

Type Package

Title Log-Concave Density Estimation in Arbitrary Dimensions

Version 1.6-10

Date 2024-09-10

Depends R (>= 3.0)

Imports MASS, mclust, mvtnorm

Suggests rgl, tkrplot

Enhances logcondens

Description Software for computing a log-concave (maximum likelihood) estimator for independent and identically distributed data in any number of dimensions. For a detailed description of the method see Cule, Samworth and Stewart (2010, Journal of Royal Statistical Society Series B, <[doi:10.1111/j.1467-9868.2010.00753.x](https://doi.org/10.1111/j.1467-9868.2010.00753.x)>).

License GPL (>= 2)

NeedsCompilation yes

Author Madeleine Cule [aut], Robert Gramacy [aut], Richard Samworth [aut], Yining Chen [aut, cre], Lutz Duembgen [ctb] (helped improve the numerical stability), Vikneswaran Gopal [ctb] (proposed the Metropolis-Hastings scheme for draw samples from a log-concave distribution), George Casella [ctb] (proposed the Metropolis-Hastings scheme for draw samples from a log-concave distribution), C. Bradford Barber [cph] (author of the Qhull library), The Geometry Center [cph], Kai Habel [cph] (author of the function that imports convex hull computation from Qhull to R), Raoul Grasman [cph] (author of the function that imports convex hull computation from Qhull to R), Alexei Kuntsevich [cph] (author of the C function for Shor's r algorithm), Franz Kappel [cph] (author of the C function for Shor's r algorithm)

Maintainer Yining Chen <y.chen101@lse.ac.uk>

Date/Publication 2024-09-11 22:53:04 UTC

Repository <https://ychen101.r-universe.dev>

RemoteUrl <https://github.com/cran/LogConcDEAD>

RemoteRef HEAD

RemoteSha bbd31770f1c83c0806e084b3427fa0a35fa31bdb

Contents

LogConcDEAD-package	2
cov.LogConcDEAD	4
dlcd	5
dmarglcd	7
dslcd	8
EMmixlcd	9
getinfoLCD	11
getweights	13
hata	14
interactive2D	15
interplcd	16
interp marglcd	17
mlelcd	18
plot.LogConcDEAD	22
print.LogConcDEAD	24
rlcd	25
rslcd	26
Index	28

LogConcDEAD-package	<i>Computes a log-concave (maximum likelihood) estimator for i.i.d. data in any number of dimensions</i>
---------------------	--

Description

This package contains a function to compute the maximum likelihood estimator of a log-concave density in any number of dimensions using Shor's r -algorithm.

Functions to plot (for 1- and 2-d data), evaluate and draw samples from the maximum likelihood estimator are provided.

Details

This package contains a selection of functions for maximum likelihood estimation under the constraint of log-concavity.

[mlelcd](#) computes the maximum likelihood estimator (specified via its value at data points). Output is a list of class "LogConcDEAD" which is used as input to various auxiliary functions.

[hata](#) calculates the difference between the sample covariance and the fitted covariance.

[dlcd](#) evaluates the estimated density at a particular point.

`dslcd` evaluates the smoothed version of estimated density at a particular point.

`rlcd` draws samples from the estimated density.

`rslcd` draws samples from the smoothed version of estimated density.

`interplcd` interpolates the estimated density on a grid for plotting purposes.

`dmarglcd` evaluates the estimated marginal density by integrating the estimated density over an appropriate subspace.

`interpmarglcd` evaluates a marginal density estimate at equally spaced points along the axis for plotting purposes. This is done by integrating the estimated density over an appropriate subspace.

`plot.LogConcDEAD` produces plots of the maximum likelihood estimator, optionally using the `rgl` package.

`print` and `summary` methods are also available.

Note

The authors gratefully acknowledge the assistance of Lutz Duembgen at the University of Bern for his insight into the objective function in `mlelcd`.

For one dimensional data, the active set algorithm in `logcondens` is much faster.

Author(s)

Yining Chen (maintainer) <y.chen101@lse.ac.uk>

Madeleine Cule

Robert Gramacy

Richard Samworth

References

- Barber, C.B., Dobkin, D.P., and Huhdanpaa, H.T. (1996) *The Quickhull algorithm for convex hulls* ACM Trans. on Mathematical Software, 22(4) p.469-483 <http://www.qhull.org>
- Chen, Y. and Samworth, R. J. (2013) *Smoothed log-concave maximum likelihood estimation with applications* Statist. Sinica, 23, 1373-1398. <https://arxiv.org/abs/1102.1191v4>
- Cule, M. L. and Duembgen, L. (2008) *On an auxiliary function for log-density estimation*, University of Bern technical report. <https://arxiv.org/abs/0807.4719>
- Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a multi-dimensional log-concave density* J. Roy. Statist. Soc., Ser. B. (with discussion), 72, 545-600.
- Gopal, V. and Casella, G. (2010) *Discussion of Maximum likelihood estimation of a log-concave density by Cule, Samworth and Stewart* J. Roy. Statist. Soc., Ser. B., 72, 580-582.
- Grundmann, A. and Moeller, M. (1978) *Invariant Integration Formulas for the N-Simplex by Combinatorial Methods* SIAM Journal on Numerical Analysis, Volume 15, Number 2, 282-290.
- Kappel, F. and Kuntsevich, A. V. (2000) *An implementation of Shor's r-algorithm* Computational Optimization and Applications, Volume 15, Issue 2, 193-205.
- Shor, N. Z. (1985) *Minimization methods for nondifferentiable functions* Springer-Verlag

See Also

[logcondens](#), [rgl](#)

Examples

```
## Some simple normal data, and a few plots

x <- matrix(rnorm(200),ncol=2)
lcd <- mlelcd(x)
g <- interplcd(lcd)
oldpar <- par(mfrow = c(1,1))
par(mfrow=c(2,2), ask=TRUE)
plot(lcd, g=g, type="c")
plot(lcd, g=g, type="c", uselog=TRUE)
plot(lcd, g=g, type="i")
plot(lcd, g=g, type="i", uselog=TRUE)
par(oldpar)

## Some plots of marginal estimates
g.marg1 <- interpmarglcd(lcd, marg=1)
g.marg2 <- interpmarglcd(lcd, marg=2)
plot(lcd, marg=1, g.marg=g.marg1)
plot(lcd, marg=2, g.marg=g.marg2)

## generate some points from the fitted density
generated <- rlcd(100, lcd)
genmean <- colMeans(generated)

## evaluate the fitted density
mypoint <- c(0, 0)
dlcd(mypoint, lcd, uselog=FALSE)
mypoint <- c(10, 0)
dlcd(mypoint, lcd, uselog=FALSE)

## evaluate the marginal density
dmarglcd(0, lcd, marg=1)
dmarglcd(1, lcd, marg=2)
```

cov.LogConcDEAD

Compute the covariance matrix of a log-concave maximum likelihood estimator

Description

This function computes the covariance matrix of a log-concave maximum likelihood estimator.

Usage

```
cov.LogConcDEAD(lcd)
```

Arguments

lcd Object of class "LogConcDEAD" (typically output from [mlelcd](#))

Details

This function evaluates the covariance matrix of a given log-concave maximum likelihood estimator using the second order partial derivatives of the auxiliary function studied in *Cule, M. L. and Duembgen, L. (2008)*.

For examples, see [mlelcd](#).

Value

A matrix equals the covariance matrix of the log-concave maximum likelihood density estimator.

Author(s)

Yining Chen

Madeleine Cule

Robert Gramacy

Richard Samworth

References

Cule, M. L. and Duembgen, L. (2008) On an auxiliary function for log-density estimation, University of Bern technical report. <https://arxiv.org/abs/0807.4719>

See Also

[hata](#)

dlcd

Evaluation of a log-concave maximum likelihood estimator at a point

Description

This function evaluates the density function of a log-concave maximum likelihood estimator at a point or points.

Usage

```
dlcd(x, lcd, uselog=FALSE, eps=10^-10)
```

Arguments

x	Point (or matrix of points) at which the maximum likelihood estimator should be evaluated
lcd	Object of class "LogConcDEAD" (typically output from mlelcd)
uselog	Scalar logical: should the estimator should be calculated on the log scale?
eps	Tolerance for numerical stability

Details

A log-concave maximum likelihood estimate \hat{f}_n is satisfies $\log \hat{f}_n = \bar{h}_y$ for some $y \in R^n$, where

$$\bar{h}_y(x) = \inf\{h(x) : h \text{ concave}, h(x_i) \geq y_i \text{ for } i = 1, \dots, n\}.$$

Functions of this form may equivalently be specified by dividing C_n , the convex hull of the data into simplices C_j for $j \in J$ (triangles in 2d, tetrahedra in 3d etc), and setting

$$f(x) = \exp\{b_j^T x - \beta_j\}$$

for $x \in C_j$, and $f(x) = 0$ for $x \notin C_n$. The estimated density is zero outside the convex hull of the data.

The estimate may therefore be evaluated by finding the appropriate simplex C_j , then evaluating $\exp\{b_j^T x - \beta_j\}$ (if $x \notin C_n$, set $f(x) = 0$).

For examples, see [mlelcd](#).

Value

A vector of maximum likelihood estimate (or log maximum likelihood estimate) values, as evaluated at the points x.

Author(s)

Madeleine Cule
 Robert Gramacy
 Richard Samworth

See Also

[mlelcd](#)

dmarglcd	<i>Evaluate the marginal of multivariate log-concave maximum likelihood estimators at a point</i>
----------	---

Description

Integrates the log-concave maximum likelihood estimator of multivariate data to evaluate the marginal density at a point.

Usage

```
dmarglcd(x=0, lcd, marg=1)
```

Arguments

x	Point (or vector of points) at which the marginal density is to be evaluated
lcd	Object of class "LogConcDEAD" (typically output from mlelcd)
marg	Which margin is required?

Details

Given a multivariate log-concave maximum likelihood estimator in the form of an object of class "LogConcDEAD", a margin `marg`, and a real-valued point `x`, this function evaluates the estimated marginal density $\hat{f}_{n,\text{marg}}(x)$, as obtained by integrating over all the other dimensions.

For examples, see [mlelcd](#).

Value

A vector containing the values of the marginal density $\hat{f}_{n,\text{marg}}$ at the points `x`.

Author(s)

Madeleine Cule
Robert Gramacy
Richard Samworth

See Also

[mlelcd](#)

dslcd *Evaluation of a smoothed log-concave maximum likelihood estimator at given points*

Description

This function evaluates the density function of a smoothed log-concave maximum likelihood estimator at a point or points.

Usage

```
dslcd(x, lcd, A=hatA(lcd))
```

Arguments

x	Point (or matrix of points) at which the smoothed log-concave maximum likelihood estimator should be evaluated
lcd	Object of class "LogConcDEAD" (typically output from mlelcd)
A	A positive definite matrix that determines the degree of smoothing, typically taken as the output of <code>hatA(lcd)</code>

Details

The smoothed log-concave maximum likelihood estimator is a fully automatic nonparametric density estimator, obtained as a canonical smoothing of the log-concave maximum likelihood estimator. More precisely, it equals the convolution $\hat{f} * \phi_{d, \hat{A}}$, where $\phi_{d, \hat{A}}$ is the density function of d -dimensional multivariate normal with covariance matrix \hat{A} . Typically, \hat{A} is taken as the difference between the sample covariance and the covariance of fitted log-concave maximum likelihood density. Therefore, this estimator matches both the empirical mean and empirical covariance.

The estimate is evaluated numerically either by Gaussian quadrature in two dimensions, or in higher dimensions, via a combinatorial method proposed by *Grundmann and Moeller (1978)*. Details of the computational aspects can be found in *Chen and Samworth (2011)*. In one dimension, explicit expression can be derived. See [logcondens](#) for more information.

For examples, see [mlelcd](#)

Value

A vector of smoothed log-concave maximum likelihood estimate values, as evaluated at the points x .

Author(s)

Yining Chen
 Madeleine Cule
 Robert Gramacy
 Richard Samworth

References

- Chen, Y. and Samworth, R. J. (2013) *Smoothed log-concave maximum likelihood estimation with applications* Statist. Sinica, 23, 1373-1398. <https://arxiv.org/abs/1102.1191v4>
- Grundmann, A. and Moeller, M. (1978) *Invariant Integration Formulas for the N-Simplex by Combinatorial Methods* SIAM Journal on Numerical Analysis, Volume 15, Number 2, 282-290.

See Also

[dlcd](#), [hatA](#), [mlelcd](#)

EMmixlcd	<i>Estimate the mixture proportions and component densities using EM algorithm</i>
----------	--

Description

Uses EM algorithm to estimate the mixture proportions and the component densities. The output is an object of class "lcdmix" which contains mixture proportions at each observation and all the information of the estimated component densities.

Usage

```
EMmixlcd( x, k = 2, y, props, epsratio=10^-6, max.iter=50,
          epsttheta=10^-8, verbose=-1 )
```

Arguments

x	Data in R^d , in the form of an $n \times d$ numeric matrix
k	The number of components, equals 2 by default
y	An $n \times k$ numeric matrix giving the starting values for the EM algorithm. If none given, a hierachical Gaussian clustering model is used. To reduce the computational burden while allowing sufficient flexibility for the EM algorithm, it is recommended to leave this argument unspecified.
props	Vector of length k containing the starting value of proportions. If none given, a hierachical Gaussian clustering model is used. To reduce the computational burden while allowing sufficient flexibility for the EM algorithm, it is recommended to leave this argument unspecified.
epsratio	EM algorithm will terminate if the increase in the proportion of the likelihood is less than this specified ratio. Default value is 10^{-6} .
max.iter	The maximum number of iterations for the EM algorithm
epsttheta	$epsttheta/n$ is the thresold of the weight below which data point is discarded from the cluster. This quantity is introduced to increase the computational efficiency and stability.
verbose	<ul style="list-style-type: none"> • -1: (default) prints nothing • 0: prints warning messages • > 0: prints summary information every n iterations

Details

An introduction to the Em algorithm can be found in *McLachlan and Krishnan (1997)*. Briefly, given the current estimates of the mixture proportions and component densities, we first update the estimates of the mixture proportions. We then update the estimates of the component densities by using `mlelcd`. In fact, the incorporation of the weights in the maximization process in `mlelcd` presents no additional complication.

In our case, because of the computational intensity of the method, we first cluster the points according to a hierarchical Gaussian clustering model and then iterate the EM algorithm until the increase in the proportion of the likelihood is less than a pre-specified quantity at each step.

More technical details can be found in *Cule, Samworth and Stewart(2010)*

Value

An object of class "lcdmix", with the following components:

x	Data copied from input (may be reordered)
logf	An $n \times k$ matrix of the log of the maximum likelihood estimate, evaluated at the observation points for each component.
props	Vector containing the estimated proportions of components
niter	Number of iterations of the EM algorithm
lcdloglik	The log-likelihood after the final iteration

Author(s)

Yining Chen

Madeleine Cule

Robert B. Gramacy

Richard Samworth

References

Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a log-concave density*, Journal of the Royal Statistical Society, Series B, 72(5) p.545-607.

McLachlan, G. J. and Krishnan, T. (1997) *The EM Algorithm and Extensions*, New York: Wiley.

See Also

[mclust](#), [logcondens](#), [plot.LogConcDEAD](#), [mlelcd](#), [dlcd](#)

Examples

```
##Simple bivariate normal data
set.seed( 1 )
n = 15
d = 2
props=c( 0.6, 0.4 )
shift=2
```

```
x <- matrix( rnorm( n*d ), ncol = d )
shiftvec <- ifelse( runif( n ) > props[ 1 ], 0, shift )
x[,1] <- x[,1] + shiftvec
EMmixLCD( x, k = 2, max.iter = 2)
```

getinfoLCD

*Construct an object of class LogConcDEAD***Description**

A function to construct an object of class LogConcDEAD from a dataset (given as a matrix) and the value of the log maximum likelihood estimator at datapoints.

Usage

```
getinfoLCD(x, y, w = rep(1/length(y), length(y)), chtol = 10^-6,
  MinSigma = NA, NumberOfEvaluations = NA)
```

Arguments

x Data in R^d , in the form of an $n \times d$ numeric matrix
y Value of log of maximum likelihood estimator at data points
w Vector of weights w_i such that the computed estimator maximizes

$$\sum_{i=1}^n w_i \log f(x_i)$$

subject to the restriction that f is log-concave. The default is $\frac{1}{n}$ for all i , which corresponds to i.i.d. observations.

chtol Tolerance for computation of convex hull. Altering this is not recommended.

MinSigma Real-valued scalar giving minimum value of the objective function

NumberOfEvaluations

Vector containing the number of steps, number of function evaluations, and number of subgradient evaluations. If the **SolvOpt** algorithm fails, the first component will be an error code (< 0)

Details

This function is used in [mlLCD](#)

Value

An object of class "LogConcDEAD", with the following components:

x	Data copied from input (may be reordered)
w	weights copied from input (may be reordered)
logMLE	vector of the log of the maximum likelihood estimate, evaluated at the observation points
NumberOfEvaluations	Vector containing the number of steps, number of function evaluations, and number of subgradient evaluations. If the SolvOpt algorithm fails, the first component will be an error code (< 0).
MinSigma	Real-valued scalar giving minimum value of the objective function
b	matrix containing row by row the values of b_j 's corresponding to each triangulation; see also mleLCD
beta	vector containing the values of β_j 's corresponding to each triangulation; see also mleLCD
triang	matrix containing final triangulation of the convex hull of the data
verts	matrix containing details of triangulation for use in dlcd
vertsoffset	matrix containing details of triangulation for use in dlcd
chull	Vector containing vertices of faces of the convex hull of the data
outnorm	matrix where each row is an outward pointing normal vectors for the faces of the convex hull of the data. The number of vectors depends on the number of faces of the convex hull.
outoffset	matrix where each row is a point on a face of the convex hull of the data. The number of vectors depends on the number of faces of the convex hull.

Author(s)

Madeleine Cule
 Robert B. Gramacy
 Richard Samworth
 Yining Chen

See Also

[mleLCD](#)

`getweights`*Find appropriate weights for likelihood calculations*

Description

This function takes a matrix of (possibly binned) data and returns a matrix containing the distinct observations, and a vector of weights w as described below.

Usage

```
getweights(x)
```

Arguments

`x` a data matrix

Details

Given an $n \times d$ matrix x of points in R^d , this function removes duplicated observations, and counts the number of times each observation occurs. This is used to compute a vector w such that

$$w_i = \frac{\# \text{ of times value } i \text{ is observed}}{\# \text{ of observations}}.$$

This function is called by `mlelcd` in order to compute the maximum likelihood estimator when the observed data values are not distinct. In this case, the log likelihood function is of the form

$$\sum_{j=1}^m w_j \log f(X_j),$$

where the sum is over distinct observations.

Value

`xout` A matrix containing the distinct rows of the input matrix `x`
`w` A real-valued vector of weights as described above

Author(s)

Madeleine Cule
Robert Gramacy
Richard Samworth

See Also

[mlelcd](#)

Examples

```
## simple normal example

x <- matrix(rnorm(200),ncol=2)
tmp <- getweights(x)
lcd <- mlelcd(tmp$x, tmp$w)
plot(lcd, type="ic")
```

hatA	<i>Compute the smoothing matrix of the smoothed log-concave maximum likelihood estimator</i>
------	--

Description

This function computes the matrix \hat{A} of the smoothed log-concave maximum likelihood estimator

Usage

```
hatA(lcd)
```

Arguments

lcd Object of class "LogConcDEAD" (typically output from [mlelcd](#))

Details

This function evaluates the the matrix \hat{A} of the smoothed log-concave maximum likelihood estimator, which is positive definite, and equals the difference between the sample covariance matrix and the covariance matrix of the fitted log-concave maximum likelihood density estimator.

For examples, see [mlelcd](#)

Value

A matrix equals \hat{A} of the smoothed log-concave maximum likelihood estimator

Note

Details of the computational aspects can be found in *Chen and Samworth (2011)*.

Author(s)

Yining Chen
Madeleine Cule
Robert Gramacy
Richard Samworth

References

Chen, Y. and Samworth, R. J. (2013) *Smoothed log-concave maximum likelihood estimation with applications* Statist. Sinica, 23, 1373-1398. <https://arxiv.org/abs/1102.1191v4>

See Also

[cov.LogConcDEAD](#)

interactive2D	<i>A GUI for classification in two dimensions using smoothed log-concave</i>
---------------	--

Description

Uses [tkrplot](#) to create a GUI for two-class classification in two dimensions using the smoothed log-concave maximum likelihood estimates

Usage

```
interactive2D(data, cl)
```

Arguments

data	Data in R^2 , in the form of an $n \times 2$ numeric matrix
cl	factor of true classifications of the data set

Details

This function uses [tkrplot](#) to create a GUI for two-class classification in two dimensions using the smoothed log-concave maximum likelihood estimates. The construction of the classifier is standard, and can be found in *Chen and Samworth (2013)*. The slider controls the risk ratio of two classes (equals one by default), which provides a way of demonstrating how the decision boundaries change as the ratio varies. Observations from different classes are plotted in red and green respectively.

Value

A GUI with a slider

Author(s)

Yining Chen
Madeleine Cule
Robert B. Gramacy
Richard Samworth

References

- Chen, Y. and Samworth, R. J. (2013) *Smoothed log-concave maximum likelihood estimation with applications* Statist. Sinica, 23, 1373-1398. <https://arxiv.org/abs/1102.1191v4>
- Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a log-concave density*, Journal of the Royal Statistical Society, Series B, 72(5) p.545-607.

See Also

[dslcd](#), [mlelcd](#)

Examples

```
## Simple bivariate normal data
## only works interactively, not run as a test example here
if(interactive()){
  set.seed( 1 )
  n = 15
  d = 2
  props=c( 0.6, 0.4 )
  x <- matrix( rnorm( n*d ), ncol = d )
  shiftvec <- ifelse( runif( n ) > props[ 1 ], 0, 1 )
  x[,1] <- x[,1] + shiftvec
  interactive2D( x, shiftvec )
}
```

interplcd

Evaluate the log-concave maximum likelihood estimator of 2-d data on a grid for plotting

Description

Evaluates the logarithm of the log-concave maximum likelihood estimator on a grid for 2-d data, for use in [plot.LogConcDEAD](#).

Usage

```
interplcd(lcd, gridlen=100 )
```

Arguments

lcd Object of class "LogConcDEAD" (typically output from [mlelcd](#))

gridlen A scalar indicating the size of the grid

Details

Interpolates the MLE over a grid.

The output is of a form readily usable by [plot.LogConcDEAD](#), [image](#), [contour](#), etc, as illustrated in the examples below.

For examples, please see [mlelcd](#).

Value

x	Vector of x -values of the grid
y	Vector of y -values of the grid
z	A matrix of the values of the log of the maximum likelihood estimator at points on the grid

Author(s)

Madeleine Cule
 Robert Gramacy
 Richard Samworth

See Also

[mlelcd](#)

interpmarglcd	<i>Finds marginals of multivariate logconcave maximum likelihood estimators by integrating</i>
---------------	--

Description

Integrates the maximum likelihood estimator of multivariate data over an appropriate subspace to produce axis-aligned marginals for use in `plot.LogConcDEAD`.

Usage

```
interpmarglcd(lcd, marg=1, gridlen=100)
```

Arguments

lcd	Output from mlelcd (of class "LogConcDEAD")
marg	An (integer) scalar indicating which margin is required
gridlen	An (integer) scalar indicating the size of the grid

Details

Given a multivariate log-concave maximum likelihood estimator in the form of an object of class "LogConcDEAD" and a margin `marg`, this function will compute the marginal density estimate $\hat{f}_{n,\text{marg}}$. The estimate is evaluated at `gridlen` equally spaced points in the range where the density estimate is nonzero. These points are given in the vector `xo`.

$\hat{f}_{n,\text{marg}}$ is evaluated by integrating the log-concave maximum likelihood estimator \hat{f}_n over the other components. The marginal density is zero outside the range of `xo`.

For examples, see [mlelcd](#).

Value

xo	Vector of values at which the marginal density is estimate is computed.
marg	Vector of values of the integrated maximum likelihood estimator at the locations xo

Author(s)

Madeleine Cule
 Robert Gramacy
 Richard Samworth

See Also

[dmarglcd](#), [mlelcd](#)

mlelcd	<i>Compute the maximum likelihood estimator of a log-concave density</i>
--------	--

Description

Uses Shor's r -algorithm to compute the maximum likelihood estimator of a log-concave density based on an i.i.d. sample. The estimator is uniquely determined by its value at the data points. The output is an object of class "LogConcDEAD" which contains all the information needed to plot the estimator using the [plot](#) method, or to evaluate it using the function [dlcd](#).

Usage

```
mlelcd(x, w=rep(1/nrow(x),nrow(x)), y=initialy(x),
  verbose=-1, alpha=5, c=1, sigmatol=10^-8, integraltol=10^-4,
  ytol=10^-4, Jtol=0.001, chtol=10^-6)
```

Arguments

x	Data in R^d , in the form of an $n \times d$ numeric matrix
w	Vector of weights w_i such that the computed estimator maximizes

$$\sum_{i=1}^n w_i \log f(x_i)$$

subject to the restriction that f is log-concave. The default is $\frac{1}{n}$ for all i , which corresponds to i.i.d. observations.

y	Vector giving starting point for the r -algorithm. If none given, a kernel estimate is used.
---	--

verbose	<ul style="list-style-type: none"> • -1: (default) prints nothing • 0: prints warning messages • $n > 0$: prints summary information every n iterations
alpha	Scalar parameter for SolvOpt
c	Scalar giving starting step size
sigmatol	Real-valued scalar giving one of the stopping criteria: Relative change in σ must be below sigmatol for algorithm to terminate. (See Details)
ytol	Real-valued scalar giving one of the stopping criteria: Relative change in y must be below ytol for algorithm to terminate. (See Details)
integraltol	Real-valued scalar giving one of the stopping criteria: $ 1 - \exp(\bar{h}_y) $ must be below integraltol for algorithm to terminate. (See Details)
Jtol	Parameter controlling when Taylor expansion is used in computing the function σ
chtol	Parameter controlling convex hull computations

Details

The log-concave maximum likelihood density estimator based on data X_1, \dots, X_n is the function that maximizes

$$\sum_{i=1}^n w_i \log f(X_i)$$

subject to the constraint that f is log-concave. For i.i.d.-data, the weights w_i should be $\frac{1}{n}$ for each i .

This is a function of the form \bar{h}_y for some $y \in R^n$, where

$$\bar{h}_y(x) = \inf\{h(x) : h \text{ concave}, h(x_i) \geq y_i \text{ for } i = 1, \dots, n\}.$$

Functions of this form may equivalently be specified by dividing C_n , the convex hull of the data, into simplices C_j for $j \in J$ (triangles in 2d, tetrahedra in 3d etc), and setting

$$f(x) = \exp\{b_j^T x - \beta_j\}$$

for $x \in C_j$, and $f(x) = 0$ for $x \notin C_n$.

This function uses Shor's r -algorithm (an iterative subgradient-based procedure) to minimize over vectors y in R^n the function

$$\sigma(y) = -\frac{1}{n} \sum_{i=1}^n y_i + \int \exp(\bar{h}_y(x)) dx.$$

This is equivalent to finding the log-concave maximum likelihood estimator, as demonstrated in *Cule, Samworth and Stewart (2008)*.

An implementation of Shor's r -algorithm based on **SolvOpt** is used.

Computing σ makes use of the **qhull** library. Code from this C-based library is copied here as it is not currently possible to use compiled code from another library. For points not in general position, this requires a Taylor expansion of σ , discussed in *Cule and Duembgen (2008)*.

Value

An object of class "LogConcDEAD", with the following components:

x	Data copied from input (may be reordered)
w	weights copied from input (may be reordered)
logMLE	vector of the log of the maximum likelihood estimate, evaluated at the observation points
NumberOfEvaluations	Vector containing the number of steps, number of function evaluations, and number of subgradient evaluations. If the SolvOpt algorithm fails, the first component will be an error code (< 0).
MinSigma	Real-valued scalar giving minimum value of the objective function
b	matrix containing row by row the values of b_j 's corresponding to each triangulation; see also the Details section above
beta	vector containing the values of β_j 's corresponding to each triangulation; see also the Details section above
triang	matrix containing final triangulation of the convex hull of the data
verts	matrix containing details of triangulation for use in dlcd
vertsoffset	matrix containing details of triangulation for use in dlcd
chull	Vector containing vertices of faces of the convex hull of the data
outnorm	matrix where each row is an outward pointing normal vectors for the faces of the convex hull of the data. The number of vectors depends on the number of faces of the convex hull.
outoffset	matrix where each row is a point on a face of the convex hull of the data. The number of vectors depends on the number of faces of the convex hull.

Note

For one-dimensional data, the active set algorithm of [logcondens](#) is faster, and may be preferred.

The authors gratefully acknowledge the assistance of Lutz Duembgen at the University of Bern for his insight into the objective function σ .

Further references, including definitions and background material, may be found in *Cule, Samworth and Stewart (2010)*.

Author(s)

Madeleine Cule

Robert B. Gramacy

Richard Samworth

Yining Chen

References

- Barber, C.B., Dobkin, D.P., and Huhdanpaa, H.T. (1996) *The Quickhull algorithm for convex hulls* ACM Trans. on Mathematical Software, 22(4) p.469-483 <http://www.qhull.org>
- Cule, M. L. and Duembgen, L. (2008) On an auxiliary function for log-density estimation, University of Bern technical report. <https://arxiv.org/abs/0807.4719>
- Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a log-concave density*, Journal of the Royal Statistical Society, Series B, 72(5) p.545-607.
- Kappel, F. and Kuntsevich, A. V. (2000) *An implementation of Shor's r-algorithm*, Computational Optimization and Applications, Volume 15, Issue 2, 193-205.
- Shor, N. Z. (1985) *Minimization methods for nondifferentiable functions*, Springer-Verlag

See Also

[logcondens](#), [interplcd](#), [plot.LogConcDEAD](#), [interpmarglcd](#), [rlcd](#), [dlcd](#), [dmarglcd](#), [cov.LogConcDEAD](#)

Examples

```
## Some simple normal data, and a few plots

x <- matrix(rnorm(200),ncol=2)
lcd <- mlelcd(x)
g <- interplcd(lcd)

oldpar <- par(mfrow = c(1,1))
par(mfrow=c(2,2), ask=TRUE)
plot(lcd, g=g, type="c")
plot(lcd, g=g, type="c", uselog=TRUE)
plot(lcd, g=g, type="i")
plot(lcd, g=g, type="i", uselog=TRUE)
par(oldpar)

## 2D interactive plot (need rgl package, not run here)
if(interactive()) {plot(lcd, type="r")}
```

```
## Some plots of marginal estimates
g.marg1 <- interpmarglcd(lcd, marg=1)
g.marg2 <- interpmarglcd(lcd, marg=2)
plot(lcd, marg=1, g.marg=g.marg1)
plot(lcd, marg=2, g.marg=g.marg2)
```

```
## generate some points from the fitted density
## via independent rejection sampling
generated1 <- rlcd(100, lcd)
colMeans(generated1)
## via Metropolis-Hastings algorithm
generated2 <- rlcd(100, lcd, "MH")
colMeans(generated2)
```

```

## evaluate the fitted density
mypoint <- c(0, 0)
dlcd(mypoint, lcd, uselog=FALSE)
mypoint <- c(1, 0)
dlcd(mypoint, lcd, uselog=FALSE)

## evaluate the marginal density
dmarglcd(0, lcd, marg=1)
dmarglcd(1, lcd, marg=2)

## evaluate the covariance matrix of the fitted density
covariance <- cov.LogConcDEAD(lcd)

## find the hat matrix for the smoothed log-concave that
## matches empirical mean and covariance
A <- hatA(lcd)

## evaluate the fitted smoothed log-concave density
mypoint <- c(0, 0)
dslcd(mypoint, lcd, A)
mypoint <- c(1, 0)
dslcd(mypoint, lcd, A)

## generate some points from the fitted smoothed log-concave density
generated <- rslcd(100, lcd, A)

```

plot.LogConcDEAD *Plot a log-concave maximum likelihood estimator*

Description

`plot` method for class "LogConcDEAD". Plots of various types are available for 1- and 2-d data. For dimension greater than 1, plots of axis-aligned marginal density estimates are available.

Usage

```

## S3 method for class 'LogConcDEAD'
plot(x, uselog=FALSE, type="ic", addp=TRUE,
     drawlabels=TRUE, gridlen=400, g, marg, g.marg, main, xlab, ylab, ...)

```

Arguments

<code>x</code>	Object of class "LogConcDEAD" (typically output from <code>mlelcd</code>)
<code>uselog</code>	Scalar logical: should the plot be on the log scale?
<code>type</code>	Plot type: "p" perspective, "c" contour, "i" image, ic image and contour, r using <code>rgl</code> (the best!)
<code>addp</code>	Scalar logical: should the data points be plotted? (as black dots on the surface for $d \geq 2$; as circles for $d = 1$)

drawlabels	Scalar logical: should labels be added to contour lines? (only relevant for types "ic" and "c")
gridlen	Integer scalar indicating the number of points at which the maximum likelihood estimator is evaluated in each dimension
g	(optional) a matrix of density estimate values (the result of a call to interplcd). If many plots of a single dataset are required, it may be quicker to compute the grid using interplcd(x) and pass the result to plot
marg	If non-NULL, this scalar integer determines which marginal should be plotted (should be between 1 and d)
g.marg	If g is non-NULL, can contain a vector of marginal density estimate values (the output of interpmarglcd). If many plots of a single dataset are required, it may be quicker to compute the marginal values to compute marginal values using interpmarglcd and pass the result to plot
main	Title
xlab	x-axis label
ylab	y-axis label
...	Other arguments to be passed to the generic plot method

Details

The density estimate is evaluated on a grid of points using the [interplcd](#) function. If several plots are required, this may be computed separately and passed to plot using the `g` argument.

For two dimensional data, the default plot type is "ic", corresponding to [image](#) and [contour](#) plots. These may be obtained separately using plot type "i" or "c" respectively. Where available, the use of plot type "r" is recommended. This uses the [rgl](#) package to produce a 3-d plot that may be rotated by the user. The option "p" produces perspective plots.

For data of dimension at least 2, axis-aligned marginals may be plotted by setting the `marg` argument. This integrates the estimated density over the remaining dimensions. If several plots are required, the estimate may be computed using the function [interpmarglcd](#) and passed using the argument `g.marg`.

Where relevant, the colors were obtained from the function `heat_hcl` in the `colorspace` package. Thanks to Achim Zeileis for this suggestion.

For examples, see [mlelcd](#).

Value

No return value, plot will display

Author(s)

Madeleine Cule
 Robert B. Gramacy
 Richard Samworth
 Yining Chen

See Also

[mlelcd](#), [interplcd](#), [interpmarglcd](#), [heat_hcl](#)

print.LogConcDEAD	<i>Summarizing log-concave maximum likelihood estimator</i>
-------------------	---

Description

Generic print and summary method for objects of class "LogConcDEAD"

Usage

```
## S3 method for class 'LogConcDEAD'  
print(x, ...)  
## S3 method for class 'LogConcDEAD'  
summary(object, ...)
```

Arguments

x	Object of class "LogConcDEAD" (typically output from mlelcd), as required by print
object	Object of class "LogConcDEAD" (typically output from mlelcd), as required by summary
...	Other arguments passed to print or summary

Details

print and summary currently perform the same function.

If there has been an error computing the maximum likelihood estimator, an error message is printed.

Otherwise, the value of the log maximum likelihood estimator at observation points is printed. The number of iterations required by the subgradient and the number of function evaluations are also printed.

Value

No return value, log MLE at observation points will be printed out on the screen.

Author(s)

Madeleine Cule
Robert B. Gramacy
Richard Samworth

See Also

[mlelcd](#)

`r1cd`*Sample from a log-concave maximum likelihood estimate*

Description

Draws samples from a log-concave maximum likelihood estimate. The estimate should be specified in the form of an object of class "LogConcDEAD", the result of a call to `mle1cd`.

Usage

```
r1cd(n=1, lcd, method=c("Independent", "MH"))
```

Arguments

<code>n</code>	A scalar integer indicating the number of samples required
<code>lcd</code>	Object of class "LogConcDEAD" (typically output from <code>mle1cd</code>)
<code>method</code>	Indicator of the method used to draw samples, either via independent rejection sampling (default choice) or via Metropolis-Hastings

Details

This function by default uses a simple rejection sampling scheme to draw independent random samples from a log-concave maximum likelihood estimator. One can also use the Metropolis-Hastings option to draw (dependent) samples with a higher acceptance rate.

For examples, see `mle1cd`.

Value

A numeric matrix with `nsample` rows, each row corresponding to a point in R^d drawn from the distribution with density defined by `lcd`.

Note

Details of the rejection sampling can be found in Appendix B.3 of *Cule, Samworth and Stewart (2010)*. Details of the Metropolis-Hastings scheme can be found in *Gopal and Casella (2010)*

Author(s)

Yining Chen

Madeleine Cule

Robert Gramacy

Richard Samworth

References

Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a multi-dimensional log-concave density* J. Roy. Statist. Soc., Ser. B. (with discussion), 72, 545-600.

Gopal, V. and Casella, G. (2010) *Discussion of Maximum likelihood estimation of a log-concave density by Cule, Samworth and Stewart* J. Roy. Statist. Soc., Ser. B., 72, 580-582.

See Also

[mlelcd](#)

rslcd

Sample from a smoothed log-concave maximum likelihood estimate

Description

Draws samples from a smoothed log-concave maximum likelihood estimate. The estimate should be specified in the form of an object of class "LogConcDEAD", the result of a call to [mlelcd](#), and a positive definite matrix.

Usage

```
rslcd(n=1, lcd, A=hatA(lcd), method=c("Independent", "MH"))
```

Arguments

n	A scalar integer indicating the number of samples required
lcd	Object of class "LogConcDEAD" (typically output from mlelcd)
A	A positive definite matrix that determines the degree of smoothing, typically taken as the output of <code>hatA(lcd)</code>
method	Indicator of the method used to draw samples, either via independent rejection sampling (default choice) or via Metropolis-Hastings

Details

This function by default uses a simple rejection sampling scheme to draw independent random samples from a smoothed log-concave maximum likelihood estimator. One can also use the Metropolis-Hastings option to draw (dependent) samples with a higher acceptance rate.

For examples, see [mlelcd](#).

Value

A numeric matrix with n rows, each row corresponding to a point in R^d drawn from the distribution with density defined by lcd and A.

Author(s)

Yining Chen

Madeleine Cule

Robert Gramacy

Richard Samworth

References

Chen, Y. and Samworth, R. J. (2013) *Smoothed log-concave maximum likelihood estimation with applications* Statist. Sinica, 23, 1373-1398. <https://arxiv.org/abs/1102.1191v4>

Cule, M. L., Samworth, R. J., and Stewart, M. I. (2010) *Maximum likelihood estimation of a multi-dimensional log-concave density* J. Roy. Statist. Soc., Ser. B. (with discussion), 72, 545-600.

Gopal, V. and Casella, G. (2010) *Discussion of Maximum likelihood estimation of a log-concave density by Cule, Samworth and Stewart* J. Roy. Statist. Soc., Ser. B., 72, 580-582.

See Also

[mlslcd](#), [rlcd](#), [hata](#)

Index

- * **EM**
 - EMmixlcd, 9
- * **classification**
 - EMmixlcd, 9
 - interactive2D, 15
- * **datagen**
 - rlcd, 25
 - rslcd, 26
- * **distribution**
 - dlcd, 5
 - rlcd, 25
 - rslcd, 26
- * **dplot**
 - dmarglcd, 7
 - interplcd, 16
 - interpmarglcd, 17
 - plot.LogConcDEAD, 22
- * **dynamic**
 - plot.LogConcDEAD, 22
- * **hplot**
 - plot.LogConcDEAD, 22
- * **iplot**
 - plot.LogConcDEAD, 22
- * **multivariate**
 - cov.LogConcDEAD, 4
 - dlcd, 5
 - dmarglcd, 7
 - dslcd, 8
 - EMmixlcd, 9
 - getinfoLCD, 11
 - getweights, 13
 - hatA, 14
 - interactive2D, 15
 - interplcd, 16
 - interpmarglcd, 17
 - LogConcDEAD-package, 2
 - mlelcd, 18
 - plot.LogConcDEAD, 22
 - print.LogConcDEAD, 24
 - rlcd, 25
 - rslcd, 26
- * **nonparametric**
 - cov.LogConcDEAD, 4
 - dlcd, 5
 - dmarglcd, 7
 - dslcd, 8
 - EMmixlcd, 9
 - getinfoLCD, 11
 - getweights, 13
 - hatA, 14
 - interactive2D, 15
 - interplcd, 16
 - interpmarglcd, 17
 - LogConcDEAD-package, 2
 - mlelcd, 18
 - plot.LogConcDEAD, 22
 - print.LogConcDEAD, 24
 - rlcd, 25
 - rslcd, 26
- * **package**
 - LogConcDEAD-package, 2
- * **smoothing**
 - dslcd, 8
 - hatA, 14
 - LogConcDEAD-package, 2
 - rslcd, 26
- contour, 16, 23
- cov.LogConcDEAD, 4, 15, 21
- dlcd, 2, 5, 9, 10, 12, 18, 20, 21
- dmarglcd, 3, 7, 18, 21
- dslcd, 3, 8, 16
- EMmixlcd, 9
- getinfoLCD, 11
- getweights, 13
- hatA, 2, 5, 9, 14, 27

heat_hcl, 24

image, 16, 23

interactive2D, 15

interplcd, 3, 16, 21, 23, 24

interp marglcd, 3, 17, 21, 23, 24

LogConcDEAD (LogConcDEAD-package), 2

LogConcDEAD-package, 2

logcondens, 3, 4, 8, 10, 20, 21

mclust, 10

mlelcd, 2, 3, 5–14, 16–18, 18, 22–27

plot, 18, 22, 23

plot.LogConcDEAD, 3, 10, 16, 17, 21, 22

print, 3

print.LogConcDEAD, 24

rgl, 4, 22, 23

rlcd, 3, 21, 25, 27

rslcd, 3, 26

summary, 3

summary.LogConcDEAD
(print.LogConcDEAD), 24

tkrplot, 15